


Seestair S50



SAFETY GUIDELINES

安全概要

RÉSUMÉ DE LA SÉCURITÉ

RESUMEN DE SEGURIDAD

セキュリティの概要

V1.0

English

Safety at a Glance



Before using this product, please read the safety summary, visit <https://www.seestar.com> to read the "User Manual," and related documents carefully. Using this product implies that you have read and accepted all terms and conditions related to this product.

This product is not suitable for children to use alone.

Warning

- Do not place the product near heat sources (stoves or heaters, etc.), and leave the product in a car on a hot day.
 - Do not mechanically impact, crush, or throw the product.
 - Do not use it outdoors in severe weather, such as strong wind (wind speed above 10.7m/s), snow, rain, lightning, and dew.
 - Do not use in environments below -10°C or above 40°C.
 - Do not place it close to devices such as cardiac pacemakers.
- Since the S50 contains magnets, it is necessary to avoid the influence of magnetization.
- Do not place heavy objects on the product.
 - Do not use any cleaning fluids on it. Cleaning with a soft dry cloth is recommended.

Notice

Dropping or bumping the S50 may damage the product, resulting in malfunction.

When using the S50, please pay attention to dust and sand protection.

Please fully open the tripod to avoid the deviation of the center

of gravity of the S50 body during work and cause it to fall. After setting up the S50, place the tripod on a flat hard, or relatively stable level surface.

Battery Safety Instructions

- Do not allow batteries to meet liquids. Do not use the battery in a rainy or wet environment. Otherwise, the battery may spontaneously ignite or even explode.
- Do not use unofficial batteries. It is recommended to use the official charging equipment provided by Seestar.
- Do not use bulging, leaking, or damaged batteries. In this case, please get in touch with Seestar or the designated agent.
- Use the battery within a temperature range of -10°C to 40°C. Excessive temperature may cause fire and explosion. Excessively low temperatures can degrade battery performance.
- Do not insert or pierce the battery with sharp objects in any way.
- The liquid in the battery is highly corrosive. If it leaks, please keep it away. In case of contact with skin or eyes, rinse immediately with plenty of water and seek medical attention.
- Keep batteries out of the reach of children. If a child accidentally swallows parts, seek medical attention immediately.
- Do not reuse the battery if it has been dropped or subjected to external shocks.
- If the battery catches fire, please use fire extinguishers in the following order: water or water cloud, sand, fire blanket, dry powder, and carbon dioxide fire extinguisher.
- After shooting for a long time, the battery is high temperature. Waiting for the battery to cool down to room temperature before charging is recommended. Otherwise, charging may be prohibited. What is the ambient temperature for charging the battery 0°C to 45°C, the ideal charging environment temperature is 22°C to 28°C, which can significantly extend the service life of the battery.

- Do not place the battery near a heat source, such as a car in direct sunlight or on a hot day, a fire, or a stove.
- Do not store the battery for a long time after it has been fully discharged to avoid the battery entering an over-discharge state, causing damage to the battery cells, and making it impossible to resume use.
- If the battery is left idle for an extended period on a critically low battery day, the battery will enter deep sleep mode. If you need to wake up the battery from a deep sleep, you need to charge the battery.

Specification

OVERVIEW	
PRODUCT NAME	Smart telescope
PRODUCT MODEL	S50
STANDARD INPUT	5V@2A
OPERATING TEMPERATURE	-10°C to 40°C
CHARGING TEMPERATURE	0°C to 45°C
S50 BODY	
BLUETOOTH	Working Frequency: 2402 MHz ~ 2480 MHz
	Output (E.I.R.P.): < 10dbm
WI-FI	WORKING FREQUENCY:
	2.4Ghz Wi-Fi: 2.400 GHz ~ 2.4835 GHz (2.4GHz ISM Band)
	5Ghz Wi-Fi: 5.15~5.35GHz, 5.47~5.725GHz, 5.725~5.85GHz (5GHz UNII Band)
	OUTPUT (E.I.R.P.):
	2.4Ghz Wi-Fi: 14Dbm;
	5.2Ghz Wi-Fi: 13Dbm;
	5.8Ghz Wi-Fi: 12Dbm;

BATTERY	Model: CH-18650/1S2P/3.7V/6.0AH (671A-SZZW)
	Capacitance: 6000mAh
	Energy: 22.2WH (0.2C)
TRIPOD	
PRODUCT NAME	TC20
WORKING HEIGHT	Maximum: 363 ±5mm
	Minimum: 233 ±5mm
TRIPOD WEIGHT	0.65Kg
SAFE LOAD-BEARING	6Kg
TRIPOD MATERIAL	Aluminum Alloy + Carbon Fiber